

CA-LED

BY WESTERN LIGHTING

**LONG-LIFE LED LIGHT SOURCE, 2 WATTS POWER
SLIM PROFILE
DIE CAST ALUMINUM
EXIT SIGN**



SPECIFICATIONS

HOUSING: Heavy-duty, die cast aluminum.

INSCRIPTION: Full 6" high x 3/4" stroke red letters behind stencil face. Twist-out chevrons are removable at job site.

LAMPS: Fixture is illuminated internally by the use of two **LED** (light-emitting diode), light arrays. LED lamps require no maintenance and consume only two watts per fixture. No LED lamps are visible. For red letters specify "-R". For green letters specify "-G".

VOLTAGE: 120v or 277v inputs are accommodated with a dual-tap LED driver.

FINISH: All white painted housing "-WH". All black painted housing "-BL". All brushed aluminum housing "-BA". For natural brushed aluminum face with black trim specify, "-ALB".

MOUNTING: Knockouts are provided on top, side and back. Canopy kit required for top and end mounting. Pendant mounting "-PND/(LENGTH)", Specify stem length required (see options).

OPTIONS:
Canopy kit "-CPY"
Flash in AC mode on 6V or 24V (AC or DC) fire alarm "-FA"
Buzzer in FA mode "-BZ"
6V DC socket & lamp "-6DC"
12V DC socket & lamp "-12DC"

CODES: Complies with ANSI/UL 924, NEC and Life Safety Code. UL LISTED.

DIMENSIONS:
EXIT HOUSING:
Height 8-1/4"
Width 13-1/2"
Depth 2-3/8"
Shallow Canopy adds 3/4" to height.

ORDERING CODE

SERIES	LAMP COLOR	VOLT	FINISH	FACES	OPTIONS
CA-LED	+	+ 120/277	+	+	+
	R Red LED G Green LED		WH BL BA ALB	SF (SINGLE FACE) DF (DOUBLE FACE)	PND/(LENGTH) FA CPY FL BZ 6DC 12DC

